



AURA – Floor / Ceiling Fan Coil Unit

CFF(A)C – CFF(A)U
Product Presentation

New Floor/Ceiling FCU: AURA

AURA is the new Fan Coil Unit for **high comfort** and **elegant design**.

It introduces a **wide range of selection** to satisfy all needs in **tertiary** as well as **home** installation.

Thanks to its **system controls** and connectivity, the unit is compatible with single, group or centrally managed solutions



New Floor/Ceiling FCU: AURA

DESIGN

The unit design has been studied by **Italian designer** to fit modern and elegant environments, both tertiary and residential



COMPACTNESS

Despite the wide range of available capacities, the unit fit **only 200mm of depth**

- Size 1-2: 790
- Size 3-4: 1.020
- Size 5-8: 1.240
- Size 9-10: 1.360




Size 11-12



Product Range

VERSIONS

AURA is available in **4 different versions**:




Product Range

CONFIGURATIONS

AURA is available in a **wide variety of configurations:**

Note: configurations in dotted areas are available only by order, contact sales network.



Product Range

CAPACITIES

Wide range of capacities:

AC Fan Motor (2 pipes)

High Fan Speed Capacity	Size	1	2	3	4	5	6	7	8	9	10	11	12
Cooling	kW	1,65	2,25	2,65	3,05	3,85	4,2	4,65	5,35	6	6,75	7,35	8,25
Heating	kW	1,85	2,35	3,05	3,15	4,1	4,3	5,2	5,7	6,15	7,15	8,2	8,5

DC Fan Motor (2 pipes)

High Fan Speed Capacity	Size	1	2	3	4	5	6	7	8	9	10	11	12
Cooling	kW	1,5	1,95	2,35	2,85	3,5	3,9	4,3	4,85	5,6	6,35	7,35	8,25
Heating	kW	1,57	2,05	2,6	2,95	3,8	4	4,7	5,25	6	7,05	8,05	8,7

Product Range

CAPACITIES

Wide range of capacities:

		AC Fan Motor (4 tubi)					
High fan speed Capacity	Size	1	3	5	7	9	11
Cooling	<i>kW</i>	1,95	2,89	4,09	5,05	6,40	7,65
Heating	<i>kW</i>	1,69	2,45	2,95	3,64	4,65	7,30


		DC Fan Motor (4 tubi)					
High fan speed Capacity	Size	1	3	5	7	9	11
Raffrescamento	<i>kW</i>	1,70	2,70	3,80	4,60	6,05	7,65
Riscaldamento	<i>kW</i>	1,40	2,30	2,88	3,35	4,60	7,50

Product Specifications

COMPONENTS

Main Components


1. Copper/Aluminum heat exchanger, with hydrophilic coating
2. PCB
3. L shaped drain pan
4. 3/4" water connections
5. Drain connection ($\Phi 18,5\text{mm}$)
6. Centrifugal fan
7. Washable filter (G2 class)
8. Galvanized sheet case



Product Specifications

INSTALLATION

The **water connections can be moved** from one side of the unit to the other by simply rotating the heat exchanger.



The optional **wired user interface** can be placed **onboard** (both sides) or installed remotely **on the wall**.



Product Specifications

WIRED USER INTERFACE

The unit is compatible with the new optional **wired User Interfaces**, both in DC and AC versions.

Touch screen and **backlit display** allow the best user experience in both onboard and wall installation.

Follow-me function, available for DC Version, allows to move the room temperature reading to the sensor present in the remote control.

DC Version



KJRP-75

AC Version




KJRP-86

	DC Version	AC Version
Touch key / Backlit	✓	✓
2 pipes / 4 pipes	✓	✓
Basic settings	✓	✓
Nr. Fan speeds	7 + AUTO	3 + AUTO
Follow-Me	✓	-
Timer	-	✓
Modbus Port	-	✓

Product Specifications

CONTROL FUNCTIONS: DC Version



CFFC and **CFFU** (DC Versions) are equipped with **electronic board**, which allows the following operations as standard:

- Optional **User interface** KJRP-75
- **0-10V** input for fan speed control
- **On/Off** input with dry contact
- Remote **alarm**
- **ELFOControl³** Compatibility
- **Modbus BMS** compatibility
- **Centralized controls** (XYE Port)
- Compatible with KJR-90 (XYE Port)



Product Specifications

CONTROL FUNCTIONS: AC Version



CFFAC and **CFFAU** (AC Versions) are equipped with **contact board**, which allows the following operations as standard:

- Optional **User Interface** KJRP-86
- **3 speed** fan control
- **ELFOControl³** compatibility through User Interface Modbus port
- **Modbus BMS** compatibility through User Interface Modbus port



Accessories

OPTIONAL ACCESSORIES



HMIDCX – User interface KJRP-75 (DC)




HMIACX – User interface KJRP-86 (AC)



BOXX – Box for wall installation of KJRP-86




EXTENX – Extension cable for KJRP-75 (2m)




3V2X – On/Off 3 way valve kit 2 pipes
(3V2SX left pipes, 3V2DX right pipes)

3V4X – On/Off 3 way valve kit 4 pipes
(3V2SX left pipes, 3V2DX right pipes)



BRVHX – Auxiliary drain pan



KDTX – Feet for floor installation

Accessories

OPTIONAL ACCESSORIES: Only for DC Version



KJR-90D – Wired user interface



KJR-150A – Group control



LONGW64 – Lonworks interface



CCM30-B – Centralized control



CCM09 – Centralized controls



CCM08 – Bacnet interface



CCM180X – Centralized controller with weekly timer 6.2"



CCM270X - Centralized controller with weekly timer 10.1"

Main Features

AURA Main Features:

- **Elegant** and **compact** design
- **AC** and **DC** Version
- Wide nr. **configurations**
- Wide range of **sizes** (1,5-8,5kW)
- Installation **flexibility**
- New optional **User Interface** (onboard/wall installation)
- **ELFOControl³ EVO** compatible
- **Modbus** port standard (DC; AC on optional Interface)



www.clivet.com



A Group Company of
 Midea